



LABORATORI
D'ENGINYERIA PAPERERA
I MATERIALS POLIMERICS



Universitat
de Girona

Product in accordance

with requirements of Directive 2004/12/CE that modifies Directive 94/62/CE
about packaging related in European standard EN 13427:2000

Paper sample referenced as SOPORTE KRAFT, manufactured by
TORRASPAPEL SA is **agree** with the evaluation requirements designed for
packaging, detailed in table 1.

Conformity number: Dir CP_11_05/SK

Issued: November, 8th 2006

Service responsible

M^a Àngels Pèlach

Laboratory responsible

Laura Barberà

R75.1-07.4 Rev.:01

Membre de:



XARXA DE CENTRES
DE SUPORT
A LA INNOVACIÓ
TECNOLÒGICA

DIRECTIVE 2004/12/CE and DIRECTIVE 94/62/CE REQUIREMENTS

Paper sample: SOPORTE KRAFT

Evaluation abstract:

Evaluation criteria	Evaluation requirement	Declaration
Requirements for measuring and verifying the four heavy metals present in packaging and their release into the environment	To guarantee levels lower than maximum allowed for components (UNE CR 13695-1)	Conform
Requirements for measuring and verifying dangerous substances present in packaging and their release into the environment	To guarantee conformity with EN 13428:2000 Standard (UNE-CR 13695-2; Directive 67/548/CE ; Directive 92/32/CEE ; Directive 2001/59/CE (28 ^a Adaptation)	Conform
Requirements for packaging waste valorisation by means of energy recovery.	To guarantee that calorific gain of waste packaging is suitable (EN 13431:2000)	Conform



LABORATORI
D'ENGINYERIA PAPERERA
I MATERIALS POLIMERICS

PACKAGING. Requirements for measuring and verifying the four heavy metals present in packaging (UNE-CR 13695-1)

1.- SAMPLE DESCRIPTION

- Paper sample SOPORTE KRAFT

2.- FACTORY

- TORRASPAPEL, S. A.

3.- TEST CONDITIONS

Total digestion of sample by means of laboratory microwave MILESTONE previously treated with acids ($\text{HNO}_3:\text{H}_2\text{O}_2:\text{HF}:\text{H}_2\text{O}$) in proportion 3:2:1:2.

Treatment program: total time: 115 min. Increase to 120°C and 5 min stabilization; increase to 150°C and 5 min stabilization; increase to 180°C and 5 min stabilization; increase to 200°C and 5 min stabilization and at last, increase to a 210°C and 5 min stabilization.

Determination of heavy metals have been made by ICP-Mass spectrometry.

4.- RESULTS

Testing date: 27/05/2006.

Metals	Results (ppm)
Mercury	< 0,25
Cadmium	< 0,25
Chromium (total)	21,91 ± 1,02
Lead	8,24 ± 0,22
TOTAL	< 100 ppm

Results expressed in mg element/Kg material

Analysis results indicate than heavy metal content is lower than 100 ppm.

5.- CONCLUSION.


Paper sample analysed referenced as SOPORTE KRAFT **is agree** with Article 11 of Directive 2004/12/CE and Directive 94/627CE about concentration levels of heavy metals in packaging and packaging wastes.

Service responsible

A handwritten signature in black ink, appearing to read 'Àngels Pèlach', enclosed within a large, loopy circular flourish.

Dra. M. Àngels Pèlach

Laboratory responsible

A handwritten signature in black ink, appearing to read 'Laura Barberà', written in a cursive style with a long horizontal stroke extending to the right.

Laura Barberà



LABORATORI
D'ENGINYERIA PAPERERA
I MATERIALS POLIMÈRICS



Universitat
de Girona

**PACKAGING. Requirements for measuring and verifying dangerous substances
present in packaging (UNE-CR 13695-2)**

1.- SAMPLE DESCRIPTION

Paper sample: SOPORTE KRAFT

2.- FACTORY

- TORRASPAPEL, S. A.

3.- CONFORMITY ANALYSIS

Sample doesn't present substances classified as dangerous for environment, or if presents, their concentration are lower than 0.1%, as indicated in Directive 67/548/CE, its modifications (Directive 92/32/CEE) and corresponding adaptations (Directive 2001/59/CE and Directive 1999/45/CE).

Analysis realized in April, 15th 2006

4.- CONCLUSION.

Paper sample analysed referenced as SOPORTE KRAFT is agree with EN 13428:2000 related in Directive 2004/12/CE and Directive 94/62/CE about presence of dangerous substances in packaging.

Service responsible

Dra. M. Àngels Pèlach

Laboratory responsible

Laura Barberà



LABORATORI
D'ENGINYERIA PAPERERA
I MATERIALS POLIMÈRICS



Universitat
de Girona

PACKAGING. Requirements for packaging recoverable in the form of energy recovery, including specification of minimum inferior calorific value (UNE-EN 13431)

1.- OBJECTIVE

The main requirement for packaging to be considered recoverable is that it provides the thermodynamic requirements to allow the incineration with energy recovery of packaging waste.

2.- SAMPLE DESCRIPTION

- Paper sample: SOPORTE KRAFT

3.- FACTORY

- TORRASPAPEL, S. A.

4.- TEST CONDITIONS

Conformity declaration with this standard has to be reinforced by next requirements:

- Material composition. Packaging composed of more than 50% (by weight) of organic content, provides calorific gain and meets the requirements to be considered recoverable
- Calorific value, when necessary, i.e., if inorganic constituents are higher than 50% (by weight).

So, first determination is the ash content as indicated in international standard ISO 1171:1997.

Sample are conditioned and 1 g of sample are weighed to the nearest 0.1 mg. Insert the sample in the furnace at room temperature. Raise the furnace temperature to 105 °C over a period of 30 min. to dry the sample. Continue heating to 525±10°C, maintaining this temperature for at least 60 min. When the incineration period is complete, remove the dish from the furnace and allow cooling until the weight is possible.

R75.1-07.5 Rev.:01

Membre de:



5.- RESULTS

Testing date: 20/05/2006

Ash content (%)	Standard deviation
15,82	0,09

Results indicate than organic matter content is 84,18% with a confidence interval of 0,10.
This sample is considered energy recoverable.

6.- CONCLUSION.


Paper simple analysed, referenced as SOPORTE KRAFT **is considered energy recoverable**,
in agree with Directive 2004/12/CE and Directive 94/62/CE.

Service responsible



Mª Angels Pèlach
Dr. Chemistry Science

Laboratory responsible



Laura Barberà
Chemistry Science Degree