Termax range

Grade	Substance Availability (g/m²)	Thickness (µm)	Phenol Content			Dynamic Sensitivity	UV offset printable	Special Features	Applications						
			BPA free	Bisphenol free	Phenol free				POS, ATM	Medical Charts	Lottery & Gaming	Labels	Tickets	Linerless	Tags
NON TOP-COATED															
Termax TES	48 55 58 65	52 60 66 74	■			Standard	■		■	■					
Termax TEX *	48 55	52 60	■	■	■	Standard	■		■	■					
Termax TFS	63 70 74 80 105 130 170	70 78 82 90 115 144 183	■			High	■			■	■	■	■		■
Termax TFX *	63 70 89 130 170	70 78 98 144 183	■	■	■	High	■			■	■	■	■		■
Termax Recy TFXr30 *	70	78	■	■	■	High	■	30% recycled content				■	■		
Termax Recy TFXr100 *	78	80	■	■	■	High	■	100% recycled content				■	■		
Termax TRF	105	112	■	■		Standard	■	Very good environmental stability			■		■		■
Termax THR	75	83	■	■		Low	■	High temperature and humidity resistance					■		
TOP - COATED															
Termax TC10	72	76	■	■		High	■	High scratch resistance, good chemical and environmental protection.				■			
Termax TC20S	72	76	■			High	■	High resistance to plasticizers, grease, water and scratching				■	■		
Termax TC20X *	59 72 77	64 76 82	■	■	■	High	■	Excellent resistance to plasticizers, grease, water, solvents and scratching	■	■	■	■	■		■
Termax TC20XB *	75	76	■	■	■	High	■	Excellent resistances, with back barrier				■			
Termax TC30X *	105 115 135 172	108 128 149 185	■	■	■	High	■	Excellent resistances and very good printability				■	■		■
Termax TCLLX *	59 72	64 76	■	■	■	High	■	Designed for linerless use, excellent resistances						■	

* Certified “No phenols added” by Ineris, the French National Institute for Industrial Environment and Risks.